

27-11-2024 50400 >

# 6.0 DC SUPER FLEX

# **Dancutter's Extremely Flexible Cutter**

This dynamic cutter can effortlessly move through several 90-degree bends in 100 mm pipes. Whether dealing with straight runs or intricate bends, the DC SUPER FLEX operates with unmatched precision.

The flexibility of the DC SUPER FLEX makes it ideal for reopening laterals, and its robustness and durability let it easily remove concrete or other hard deposits from pipelines.

When you are cutting, milling, and grinding in pipes ranging from 75 – 150 mm / 3'' – 6'', regardless of the material – be it PVC, concrete, cast iron, or steel – the DC SUPER FLEX stands out as the perfect tool.



# **Specifications**



### **PIPE DIAMETER**

Dia. 75 - 150 mm, 3" - 6"



### **SUPPLY HOSE OPTIONS**

25 or 50 metres, 82 or 164 ft



# **BENDS**

45° - 90°



# **EXPANSION / EXTRACTION**

60 mm - 2,4"



### **ROTATION**

360° continuously



### **GRINDS, MILLS AND CUTS**

Pvc, liner, concrete, iron, cast iron, stainless steel

### **Technical support**

If you experience problems with the cutter or if you have any technical questions, please write to **support@dancutter.dk** 

## Order

If you need spare parts or cutting heads, please write to **order@dancutter.dk** 

# DC SUPER FLEX



27-11-2024 50400 >



# **Highlights**

Extremely flexible in 45° and 90° bends

360°-degree continuous rotation

High-quality stainless-steel alloy

12" colour display

Cuts, grinds, and mills in all materials

User friendly

Precise control

Toolbox and centring tool with brushes are standard accessories

# **Technical data**

Pipe diameter: 75 - 150 mm / 3" - 6"

DC SUPER FLEX can be operated by just one person

The DC SUPER FLEX comes with either a 25 m or a 50 m hose

The control unit features inlet and outlet sockets for connecting a video recorder, computer, external camera, or FPV headset (optional accessory)

12" colour display

Spray nozzle for cleaning the camera



### **AIR SUPPLY**

650 l/min, 22 cfm



## **GRINDER**

15000 rpm



## AIR PRESSURE

Max 10 bar, 145 psi



### **POWER SUPPLY**

110 / 240 VAC - LN



### WEIGHT

25 m: 58 kg, 128 lb/50 M: 71 kg, 156.5 lb



### STAINLESS - STEEL FRAME

L: 1000 MM / W: 500 mm / H: 1030 mm L: 39.37" / W: 19.69" / H: 40.55"

### Standard and extra accessories for DC SUPER FLEX

We offer a versatile range of accessories and spare parts for your Dancutter solutions.

Get an overview on www.dancutter.com